

9001 KIT DIMMER 2000W AND REMOTE CONTROL

230V wireless wall fixing receiver with dimmer function for resistive/infrared heaters up to 2000W. Dimming on 3 pre-set levels selectable with the wireless transmitter. If controlled with a 4-channel transmitter the first 3 channels activate the levels. The 4th channel do the switching off. Input for manual control. IP54 protection.

Wireless. Remote control with wireless transmitters and with wall fixing support.

Selectable power 100%, 66%, 50%, OFF

Easy installation. Suitable for false ceiling.

Input. Push-button input for manual commands.

Characteristics:

- Dimmer function on 3 levels
- Power supply 230V
- Heater control up to 2000W

DIMMER TECHNICAL SPECIFICATIONS

Power supply 230V

Minimum settable load 25W

Maximum settable load 2000W

Operating temperature range -20°C +50°C

Protection level IP54

Dimensions 165 x 64 x 30 mm

REMOTE CONTROL TECHNICAL SPECIFICATIONS

Power supply 3V ± 10% (lithium battery CR2032)

Operating temperature -10°C +55°C



9003 KIT PRESENCE DETECTOR AND RECEIVER

2-channel presence detector via radio with battery for external use. ON/OFF function. IP44 protection. Mod 9003 senses the presence of human body by its warm and not only movement.

Possible settable functions:

- Light intensity: for switch on and off depending by environment brightness
- Activation distance: adjustable detection range
- Adjustable ON/OFF time

RECEIVER TECHNICAL SPECIFICATIONS

Power supply 230Vac

Maximum resistive load 2000W (x 2 outlets)

Operating temperature range -20°C +50°C

Protection IP54

Dimensions 205 x 145 x 85 mm

PRESENCE DETECTOR TECHNICAL SPECIFICATIONS

Power supply 6Vdc (UM-3 AA battery 1.5V x 4)

Signal range approx 100m (free space)

Detecting range 12m/180°



ON/OFF time adjustable from 5 sec. to 5 min.
 LUX adjustable from 5 LUX to ∞
 Protection IP44
 Dimensions 87 x 125 x 120 mm

9004 KIT RECEIVER AND REMOTE CONTROL

Kit 9004 permits you to switch On and Off up to two MO-EL heaters separately.

RECEIVER TECHNICAL SPECIFICATIONS

Power supply 230Vac
 Maximum resistive load 2000W (x 2 outlets)
 Operating temperature range -20°C +50°C
 Protection IP54
 Dimensions 205 x 145 x 85 mm

REMOTE CONTROL TECHNICAL SPECIFICATIONS

Power supply 3V \pm 10% (lithium battery CR2032)
 Operating temperature -10°C +55°C



724 DIMMER 4 CHANNELS

Zone dimmer for controlling remotely the power of infrared heaters.
 Up to four MO-EL heaters with power dimming and separated ON/OFF
 Easy to connect.
 CE GS certified.
 Dimensions: 28 cm high, 22 cm wide, 12 cm deep.
 Each Channel can operate up to 2000W
 Power Supply 400V 50Hz

